

**PAT-NO:** JP362021112A  
**DOCUMENT-IDENTIFIER:** JP 62021112 A  
**TITLE:** SUBMARINE OPTICAL CABLE  
**PUBN-DATE:** January 29, 1987

**INVENTOR-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
-------------	----------------

FUNAKI, YASUSHI	
-----------------	--

KATO, KUNIIHIKO	
-----------------	--

MOCHIZUKI, KENICHI	
--------------------	--

**ASSIGNEE-INFORMATION:**

<b>NAME</b>	<b>COUNTRY</b>
-------------	----------------

OCEAN CABLE CO LTD	N/A
--------------------	-----

**APPL-NO:** JP60160259

**APPL-DATE:** July 22, 1985

**INT-CL (IPC):** G02B006/44

**US-CL-CURRENT:** 385/101

**ABSTRACT:**

**PURPOSE:** To increase interlayer adhesive strength, to improve the pressure- tightness of a submarine optical cable, and to eliminate the cause of a water run by performing the matte working of the external surface of a metallic tube which constrains a tensile strength wire and molding an insulator layer thereupon by extrusion.

CONSTITUTION: A metallic tape unwound from a metallic tape supply drum 15 is extended longitudinally along a cable wound with the high strength wire and formed into a cylinder gradually by a metallic tape forming roll 16. Then, the seam of the metallic tape is welded together by a next metallic tape welder 17 and the welded metallic tube 5 is formed almost round by a metallic tube forming roll 18 and passed through a drawing die 19 to increase its interlayer adhesive strength. A matte working roll 20 is pressed against the surface of the metallic tube 5 passed through the drawing die 19 among plural rolls 20a~20d to make its surface matte. The tube is wound temporarily around a take-up drum 21 and sent to an extrusion molding process where the next insulator layer is formed.

COPYRIGHT: (C)1987,JPO&Japio